



1 FleetCam 3.0 MDVR

MDVR must be mounted flat and straight with the access door facing front or rear side of the vehicle.

2 DMS (AI Driver) Camera

Gets mounted to the dashboard on the left or right side of the steering wheel.

3 ADAS (AI Road) Camera

- Heavy-Duty Vehicles
- Adhere camera to the center of the bottom of the windshield just above the resting wiper path.
  - Clean mounting surface with rubbing alcohol prior to mounting.
- Light-Duty Vehicles
- Adhere camera to the center of the windshield in the top two inches of the windshield wiper path.
  - Clean mounting surface with rubbing alcohol prior to mounting.

4 Auxiliary Cameras

Auxiliary cameras to be mounted at customers desired locations (i.e., side cameras, rear camera, cargo camera).

5 V-Display (Optional)

- Adhere the V-Display to the top of the dashboard in a location easily viewable to the driver that does not obstruct the drivers line of vision.
- Clean surface with rubbing alcohol before adhering.

6 Cellular (LTE) Antennas

Cellular antennas get mounted towards the uppermost part of the windshield.

7 Dead-Reckoning GPS Antenna

Antenna must be mounted as straight as possible on top of vehicle dashboard. Antenna wire must come out of the rear side of the antenna.

8 Power Harness

- Red wire to constant power source (+)
- Yellow wire to ignition power source(+)
- Ground wire to chassis ground(-)

9 Lane Departure (Optional)

- Connect Sensor Input 7 **Black/Blue** to left turn signal (+)
- Connect Sensor Input 8 **White/Blue** to right turn signal (+)

