



1 FleetCam 3.0 MDVR

MDVR must be mounted flat and straight with the access door facing front or rear side of the vehicle

2 DMS (AI Driver) Camera

Gets mounted to the dashboard on the left or right side of the steering wheel.

3 ADAS (AI Road) Camera

Heavy-Duty Vehicles

- Adhere camera to the center of the bottom of the windshield just above the resting wiper path.
- Clean mounting surface with rubbing alcohol prior to mounting.

Light-Duty Vehicles

- Adhere camera to the center of the windshield in the top two inches of the windshield wiper path.
- Clean mounting surface with rubbing alcohol prior to mounting.

4 Auxiliary Cameras

Auxiliary cameras to be mounted at customers desired locations (i.e., side cameras, rear camera, cargo camera).

5 V-Display (Optional)

- Adhere the V-Display to the top of the dashboard in a location easily viewable to the driver that does not obstruct the drivers line of vision.
- Clean surface with rubbing alcohol before adhering.

6 Wi-Fi Antenna

Mount the Wi-Fi antenna as close as possible to the vehicle's Wi-Fi source.

7 Dead-Reckoning GPS Antenna

Antenna must be mounted as straight as possible on top of vehicle dashboard. Antenna wire must come out of the rear side of the antenna.

8 Power Harness

Red wire to constant power source (+)
Yellow wire to ignition power source (+)
Ground wire to chassis ground (-)

9 Lane Departure (Optional)

- Connect Sensor Input 7 Black/Blue to left turn signal (+)
- Connect Sensor Input 8 White/Blue to right turn signal (+)

