



## 1 FleetCam Pro Camera

### Light Duty Vehicles:

- Adhere the camera to the center of the windshield directly under the rear view mirror.
- Clean the mounting surface with rubbing alcohol before mounting.

### Heavy Duty Vehicles:

- Adhere the camera to the center of the windshield in the top 2 inches of the wiper path.
- Clean the mounting surface with rubbing alcohol before mounting.

- If the center of the windshield is an obstruction to the driver's line of vision the FleetCam Pro can be offset towards the passenger side of the windshield.
- **Maximum offset** measurement allowed is **4 inches**.
- **Adjust camera** position to be **as vertical as possible**.

## 2 Power Box

- Used to sense vibration
- Adhere the power box to the chassis of the vehicle via double-sided tape.

## 3 Input/Output Wiring

- Gray - Sensor Input 1
- Yellow - Sensor Input 2
- Blue - Sensor Input 3
- Green - Sensor Input 4

## 4 IOX - Connections

### FleetCam Connection

- Plugs into FleetCam Pro

### IOX Male Connection

- Plugs into Geotab device

### IOX Female Connection

- Spare connection to attach additional Geotab accessories

## 5 Video In/Out Cable

Used for LCD and auxiliary cams.

## 6 LCD

- Connect the **Red** wire to **constant power source(+)**.
- Connect the **Orange** wire to **ignition power source(+)**.
- Connect the **Black** wire to **chassis ground(-)**.

