



# BETEN

BETEN-ATT, BETEN-TMO



## FEATURES & BENEFITS

- Configurable alerts
- Geo-location settings
- 5+ year battery life
- Easy to install
- IP67 waterproof casing

## Capabilities

Utilizing the latest in cellular technology, the BeTen is the top-tier end-to-end asset tracking solution you need to better monitor your assets such as cargo, trucks, construction equipment, and large scale tools.

## Pin-Point Location

BeTen is the simplest way to monitor your assets. Never lose your equipment again as the BeTen device pairs with the IntelliHub® software to tell you the exact locations of your valuables every 24 hours.

## Easy to Install

The simple design of the BeTen means it's easy to attach to your equipment. Simply attach the BeTen at the two screw points and go. Plus, with an IP67 protection rating, the BeTen is both dust-tight and waterproof.



# BETHERE

BETEN-ATT, BETEN-TMO

## SPECIFICATIONS

### GENERAL

Communication	CAT M1 /CAT NB1/NB2
Location Technology	High accuracy Gen9 with concurrent GNSS (GPS, GLONASS, BeiDou, Galileo, and QZSS)
Operation Voltage	3.5 – 3.6V
Battery	Battery Pack of 2AA (3.6V Lithium-Ion, 5600 mAh) non-rechargeable batteries

### GPS

GPS Receiver	Gen9 VT of Qualcomm (GPS, GLONASS, BeiDou, Galileo, and QZSS)
GPS Accuracy	<3 meters CEP-50

### CELLULAR

Cellular Data	LTE CAT M1 Packet Data (CoAP/UDP) / CAT NB1/NB2 Packet Data CoAP/LwM2m/UDP
SIM	4FF (nano SIM)
Sensor Operational Accuracy	Temperature: -40, +185; Absolute accuracy $\pm 32.9^{\circ}\text{F}$ Humidity: Absolute accuracy $\pm 3\%$ RH Pressure: 300...1100hPa, Absolute accuracy $\pm \text{hPa}$
3-Axis Accelerometer	Motion (*Shock & tilt trigger use case specific)

### CERTIFICATIONS

Certifications	CTIA (PTCRB/OTA), FCC/IC
Vibration & Shock	MIL-STD 810G
Cellular Carriers	AT&T/T-Mobile
Additional Carriers	Verizon, DT, Telefonica, Vodafone, Ericsson, Orange
Ingress Protection	IP67

### PHYSICAL

Operating Range	-40 to +167°F (Batteries, Enclosure)
Humidity	95% R.H. @ 122°F non-condensing
Dimensions	3.96 in x 2.22 in x 1.32 in
Weight	0.4 lbs.