

FleetCam® Mini Dome Camera

FC-CAM-D-AHD-2.8



FEATURES & BENEFITS

- Anti-vibration design
- Lockable positioning
- Rugged and tamper-resistant
- Built-in microphone
- IP54 Rating
- IR for nighttime

FleetCam® Mini Dome Camera

The FleetCam® Mini Dome Camera is made to weather the toughest conditions. With a durable metal exterior, this camera is vibration and thermally tested making it the preferred choice for a variety of applications. Utilizing the latest in CMOS imaging sensors, it provides outstanding image quality in both day and nighttime driving conditions. The camera also includes a built-in microphone to capture clear audio as events occur giving you the information you need to reduce risk and improve driver safety.

SPECIFICATION

CMOS:	1/3" 1.3M pixel CMOS	Audio:	Built-in Mic
Resolution:	1280(H) x 720(V)	Power:	DC12V ± 10%
Minimum Illumination:	0.1Lux (IR off) /0Lux (IR on) F1.2	Consumption (Max):	120m A/DC 12V ± 5%
IR Distance	5~8m	Working Temperature:	-40°C~70°C
Lens:	2.8mm	Dimension:	69mm(W) * 55.5mm(H)
FOV:	2.8mm H*V 88° * 50°	Weight:	About 168g
Video Output:	AHD video output 4pin DIN JACK		



FORWARD THINKING
Stay ahead of the other guys.

FleetCam[®] Mini Dome Camera

DIMENSIONS

