

FleetCam® Side Camera

FC-CAM-S-AHD-BLK



FEATURES & BENEFITS

- EASY INSTALLATION MECHANICAL DESIGN
- NOISE REDUCTION TECHNOLOGY
- IP67 WATERPROOF & VANDALPROOF HOUSING
- FOUR VIEWING ORIENTATIONS
- 3.6MM FIXED LENS
- 12 LED VISION RANGE

FleetCam® Side Camera

The FleetCam Side Camera provides drivers with a clear view of the sides and blind spots of your trucks, trailers, busses, and more. The Cameras are dust-tight and waterproof and provide automatic night vision for crystal view even at night.

SPECIFICATION	
Picture Element	1280(H)x 720(V)
Signal Format	PAL /NTSC
Horizontal Resolution	720P
Pick Up Device	1/4" AR0130 CMOS sensor
Scanning System	PAL:625 TVL; NTSC: 525 TVK 2:1 Interlace
Sensitivity	0 Lux (Infrared LED On, at F1.2)
Infrared Spectrum	850nm
Infrared LED	12LEDs
Infrared LED Range	12m
Minimum Illumination	0.05LUX (F1.2) color mode; 0 Lux (IR ON)
S/N Ratio	≥44dB
Video Output	1.0Vp-p/75Ω
AGC	Auto
White Balance	Auto
Backlight Compensation	Auto
Exposure Mode	AI/EE
Electronic Shutter	1/50~1/100000
Day/Night	Auto
Lens	Mega-pixel 3.6mm (2.8mm/6.0mm for optional)
Lens Mount	M12xP0.5mm Thread
Infrared LED	12 LEDs
Infrared LED Range	8m
Power Supply	12V DC ±10%
Power Consumption	160mA ±10%
Operation Temperature	14°F - +140°F (-10°C - +60°C)
Protection Rating	IP67
Dimensions	3.07 x 62 x 2.2 in (78x62x56 mm)
New Weight	.66 lbs. (300g)