Auxiliary Camera Bundle for FleetCam® Pro · FC-CAM-AHD-DOC

Pick the Camera That Fits Your Needs.

- HD (720p) video with infrared night recording
- Everything needed to add a channel in one box
- Camera cable connects directly to your FleetCam Pro
- AHD extension cable sized to your vehicle (5m, 9m, or 15m)
- 1 AHD camera — your choice of interior dome or exterior camera

Pick the Camera for the Job

The interior mini dome is tamper-resistant, vibration-tested, and records audio through a built-in mic. The exterior camera is weatherproof (IP66) and dust-tight with a sun shield, built to ride outside in any weather.

Sees at Night, Both Ways

Both options carry infrared illumination — the dome reaches 5–8m, the exterior camera 15–30 ft — and adjust automatically between day and night. The 2 AM loading dock gets the same coverage as the noon delivery.

An Added Layer for Reversing and Maneuvering

An exterior view provides additional visibility and accountability, with HD footage captured while backing and maneuvering.

Plug In, Aim, Done

The camera cable easily connects the camera straight to your FleetCam Pro. Extension cables come in three sizes, matching the length of your vehicle and needs for optimal camera placement.

Auxiliary Camera Bundle for FleetCam® Pro · FC-CAM-AHD-DOC

Your FleetCam Pro is already watching the road and the cab. This bundle extends it one camera at a time — into the cargo area, over the rear bumper, wherever incidents keep happening off-screen. One camera, the camera connection cable that ties it to your Pro, and an extension cable matched to the run: nothing extra to source, nothing left out of the box.

Specifications

Interior — FleetCam® Mini Dome (FC-CAM-D-AHD-2.8)

Sensor	1/3″ 1.3MP CMOS
Resolution	1280 (H) x 720 (V)
Min. Illumination	0.1 Lux (IR off) / 0 Lux (IR on), F1.2
Lens / FOV	2.8mm; 88° x 50°
IR Distance	5–8 m
Video Output	AHD video output, 4-pin DIN jack
Audio	Built-in mic
Power	DC 12V ±10%; 120 mA max
Housing	Metal, IP54, anti-vibration, lockable positioning
Operating Temp	-40 to +70 °C
Dimensions	69 mm (W) x 55.5 mm (H); ~168 g

Exterior/Rear — FleetCam® Outdoor AHD (FC-CAM-OS-AHD-2.8)

Sensor	1/3″ 1.3MP CMOS
Resolution	1280 x 720; NTSC
Min. Illumination	0 Lux @ F1.2
Lens	2.8mm
IR Distance	15–30 ft
S/N Ratio	≥50 dB
Video Output	AHD coaxial HD, 4-pin aviation cable
Image	Auto electronic shutter, white balance, gamma 0.45
Power	DC 12V; 130–150 mA max
Housing	IP66 waterproof & dust-tight, sun shield, anti-vibration, lockable angles
Operating Temp	-4 to +122 °F
Weight	380 g (~0.84 lbs)

Cabling & Compatibility

Camera Cable	Video input/output cable; connects to the FleetCam® Pro
Extension Cable	AHD extension — 5m, 9m, or 15m
Compatibility	FleetCam® Pro

© 2026 Forward Thinking Systems. All rights reserved. Specifications subject to change without notice.